# DGM2937SVAT



HD 1080P



**Human Detection** 



H.265

zoom

20X Optical

700m







PTZ



WDR

WDR

PoE



MIC built-in




#### Al-based 2MP H.265 20X Speed Dome IP Camera

#### O FEATURES

- Starlight visibility to offer clear & color images even at night
- Zoom lens of f4.7 ~ f94mm with 20X optical zoom, suitable for various monitoring environments
- Al-based human detection supported to avoid false detection alarms
- PTZ control for seamless monitoring:
- **ONVIF** standard supported to simplify system integration
- POE (Power-over-Ethernet) support to eliminate the use of power cables and reduce installation costs
- Microphone built-in for audio recording and line out support for audio broadcasting
- IR effective range up to 120 meters for night surveillance
- WDR to increase image recognizability in overexposure and dark areas
- **Remote Surveillance** Compatible with Internet Explorer 6 and above, Microsoft Edge & Google Chrome

#### O DIMENSIONS





### **O SPECIFICATIONS**

Device		
Image Sensor		1/2.8" SONY CMOS
Max. Resolution		1920 x 1080
Lens		f4.7 ~ 94mm / F1.6 - F3.5
Viewing Angle		Tele 2.9° ~ Wide 64° (Diagonal)
Min Illumination		0.001 Lux (IR LED off), 0 Lux (IR LED on)
Shutter Speed		AUTO, 1/25s ~ 1/100000s
IR LED		8 units
IR Effective Distance		Up to 120 meters
Day / Night		YES
WDR Mode		YES (120dB)
RTC (real-time clock)		YES
Video		
Compression		H265 / H.264
Video Resolution	Main Stream	2MP (1080P) / 720P / D1
	Sub Stream	D1 / VGA / 640x360 / CIF
Frame Rate		2MP @ 30FPS
Video Profile		High profile / Main profile / Base profile
Multiple Video Streaming		2 streams
Bitrate Control		512Kbps - 12Mbps, VBR/CBR
Image Enhancement		WDR / BLC / HLC / 2D DNR / 3D DNR / AWB / MWB / AGC
Day / Night Switch		Auto / Color / (B/W) / Timing
Forced Anti-flicker		YES
Defog		YES
White Balance		Auto / Manual
Image Orientation		Rotate / Mirror
Privacy Mask		YES
Text Overlay		YES
OSD Title		Location / font size / text configurable; text input (English & Chinese characters) and imag upload (BMP) supported
Audio		
Microphone built-in		YES
Line out		YES
Encoding		G.711-u / G.711-a
Audio Adjustment		YES
Alarm & Event		
Detection Mode		Motion / Human Detection
Detection Schedule		YES
Motion Detection Area		1x1, 2x2, 3x2, 3x3, 4x3, 4x4, 8x8, 16x16, 22x18
Detection Alert		Audio alert with customized mp3 audio file(s)

.\*The specifications are subject to change without notice. .



## • SPECIFICATIONS (CONTINUED)

Network	
LAN Port	RJ45 connector x 1 / 4KV lightning-proof
LAN Speed	100Mbps Based-T Ethernet
Supported Protocols	HTTP / RTSP / FTP / SMTP / DHCP / NTP / NFS / RTMP
ONVIF Compatible	Onvif 17.06 compatible
Number of Online Users	6
Remote Access	Internet Explorer 6 and above (recommended), Microsoft Edge & Google Chrome
PTZ Mechanism	
Pan Range	360° continuous rotation
Pan Speed	0.5° ~ 60°
Tilt Range	-15° ~ 90°/s
Zoom Ratio	20X Optical Zoom
Proportional Zoom	YES
Preset Points	Up to 255 preset points
PTZ Mode	Cruising / Auto Pan
General	
Web Interface Language	English, Traditional Chinese, Simplified Chinese, Russian, German, Italian, Turkish, Kore
Operating Temperature	-30℃ ~ 60℃
Operating Humidity	10% ~ 90%RH
POE	IEEE 802.3at
Power Source (±10%)	PoE / DC12V
Power Consumption (±10%)	< 20 W
Net Weight (kg)	2.5
Casing	IP66
Minimum Web Browsing Requirements	<ul> <li>Intel core i3 or higher, or equivalent AMD</li> <li>2GB RAM</li> <li>AGP graphics card, Direct Draw, 32MB RAM</li> <li>Windows 10, Windows 8, Windows 7, DirectX 9.0 or later</li> <li>Internet Explorer 6 and above (recommended), Microsoft Edge &amp; Google Chrome</li> </ul>

.\*The specifications are subject to change without notice.